

## ATEN CL5716IN

**ProdCode: ATENCL5716IN**

1-Local/Remote Shared Access 16-Port PS/2-USB VGA Single Rail LCD KVM over IP switch with 19" LED-backlit LCD monitor



[\[Download Images\]](#) (.zip file)

### Features

- 1-Local/Remote Shared Access 16-Port PS/2-USB VGA Single Rail LCD KVM over IP switch with 19" LED-backlit LCD monitor
- Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- Integrated KVM console with 19" LED-backlit LCD monitor in a Slideaway™ housing
- 1 remote bus for KVM over IP access-allowing IT administrators to remotely monitor and control upto 16 servers
- Mouse DynaSync™-automatically synchronizes the local and remote mouse movements

The CL5716I Slideaway™ LCD KVM Switch is a control unit that allows access to multiple computers from a single PS/2 or USB KVM (keyboard, video, and mouse) console. A single CL5716I can control up to 16 computers. Up to 15 additional KVM switches can be daisy-chained to the CL5716I, so that up to 256 computers can all be controlled from a single KVM console.

The CL5716I LCD KVM Switch is an IP-based KVM control unit that allows both local and remote operators to monitor and access multiple computers. Remote users access the switches over the Internet by means of a web browser using TCP / IP for its remote communications protocol. The CL5716I supports up to 32 concurrent user logins for a single-bus computer access. A built-in feature that resembles an Internet chat program - the Message Board - lets them communicate with each other. The ability to exchange information in real time allows them to cooperatively manage the installation in a smooth and efficient manner.

The CL5716I offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 19" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. In addition, since the CL5716I is built on a modular design, the KVM section can be detached from the switch section for convenient maintenance and repair.

Among CL5716I's other outstanding features, the Panel Array Mode provides the ability to monitor the video output of the servers on the installation; while the Mouse DynaSync™ feature automatically synchronizes the local and remote mouse pointer movements for perfect alignment regardless of what the mouse acceleration settings on the server are.

The CL5716I supports the highest security protocols, such as TLS 1.2 encryption for the browser, and RC4 encryption for secure keyboard, mouse, and video data transmission. For easier and more efficient user management integration, the CL5716I also supports authentication and authorization via 3rd party authorized servers, such as RADIUS, LDAP, LDAPS, and MS Active Directory.

Note: Optional rack mount kits are available.

### **In the box:**

- 1x CL5716I LCD KVM over IP Switch with standard Rack Mount Kit
- 2x Custom KVM Cables (VGA, USB; 1.8 m/6 ft)
- 1x Custom Console Cable (VGA, USB, PS/2; 27 cm/0.88 ft)
- 1x Firmware Upgrade Cable
- 1x Power Cord
- 1x User Instructions

---

### **Need Further Support?**

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries

---

or provide further information or marketing collateral as needed.

**Contact Us:**

- Marketing - [marketing@holdan.co.uk](mailto:marketing@holdan.co.uk)
- Sales - [sales@holdan.co.uk](mailto:sales@holdan.co.uk)
- Technical Enquiries - [techsales@holdan.co.uk](mailto:techsales@holdan.co.uk)
- Request Demo product loans - [demo@holdan.co.uk](mailto:demo@holdan.co.uk)

We value your partnership and are committed to ensuring a successful product launch.  
Thank you for your continued support.