

ATEN KE6940AT

ProdCode: ATENKE6940T

DVI-I Dual Display KVM over IP Transmitter



[\[Download Images\]](#) (.zip file)

Features

- DVI-I Dual Display KVM over IP Transmitter
- Supports 1Gbps SFP fiber module expansions up to 10 km
- Supports power/network failover – dual DC jacks for power redundancy and 1 RJ45 & 1 SFP fiber ports for network failover to ensure constant availability for mission-critical applications
- Superior video quality – up to 1920 x 1200 @ 60 Hz; 24-bit colour depth
- Supports digital (DVI) or analogue (VGA) video output

The KE6940A extender is consisted of a high performance IP-based transmitter (KE6940AT) that connects to the computer and a receiver (KE6940AR) that provides console access from a separate location. The KE6940A allows extended access of computer systems remotely via USB consoles (USB keyboard, USB mouse, DVI monitor) over intranet, enabling users to place the computer system in secure and temperature controlled environments, which maybe isolated from users' workstation.

The KE6940A DVI-I Dual Display KVM over IP Extender supports two DVI displays at each end and provides lossless and low latency video transmissions up to 1920 x 1200

@ 60Hz.

The KE6940A support connections via an RJ-45 port or a SFP slot. The transmitter and receiver can be connected either directly to each other, or via a high-speed network over a copper-based or fiber-based LAN. Connecting via the SFP slot with 1Gbps SFP fiber module expansions on fiber optic network, you can extend transmission distances up to 10km. The KE6940A also features dual power supplies for redundancy to ensure dependable services.

As an IP-based matrix extender, the KE6940A can be used as a point-to-point / point-to-multipoint / multipoint-to-point extender, or integrated into a KVM over IP Matrix System (multipoint-to-multipoint) when combined with the KVM over IP Matrix Manager (CCKM), providing more flexible applications in different working environments.

Implementing the CCKM with KE6940A, IT administrators can benefit from advanced features such as auto detection of all KE6940A devices on the same subnet for the sake of fast installation or configuration, username/password authentication and authorization, and the ability to define different types of connections that can be switched and shared. Security features also provide extra protection, supporting AES-128bits encryption for secured data transmissions, while RADIUS, LDAP, AD or remote user authentication provides an added layer of connection security. Moreover, with an OSD, RS-232 support, and Auto MDIX, the KE6940A is the most cost-effective and convenient way to get a full digital extension from anywhere on the intranet.

In the box:

- 1x KE6940AT DVI-I Dual Display KVM over IP Transmitter
- 1x Power Adapter & Power Cord
- 1x KVM Cable (DVI-D, USB, Audio; 1.8m/6ft)
- 1x DVI-D Cable 1.8 m
- 1x Foot Pad Set (4 pcs.)
- 1x Mounting Kit
- 1x User Instructions

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch.
Thank you for your continued support.