

Cartoni Lifto 25/S Twin

ProdCode: CARKPTZ0302

Twin Motorized elevation column optimized for use with PTZ cameras



[\[Download Images\]](#) (.zip file)

Features

- Twin Motorized elevation column optimized for use with PTZ cameras
- Cartoni Lifto 25/S Twin Motorized Elevation Column with remote control unit, SDS tripod, smart lock spreader & rubber feet
- Extremely silent elevation motor
- Height range 118cm (46,8") to 380 cm (150")
- Maximum payload 20 kg (44 lbs)
- Smart deployment tripod for great torsional rigidity and fast set-up
- Bluetooth & wired remote control unit
- 3 position pre-settings for fast routine repositioning
- Safe release camera attachment for PTZ cameras with camera safety ring
- XLR connector
- Optional Dolly for easy movements around location

The Cartoni Lifto 25/S Twin was specifically designed for PTZ cameras, bringing extremely smooth on-air quality vertical movements and creativity to enhance productions. This solution adds to the Pan & Tilt, and zoom control, additional height movement as a natural feature.

Lifto 25/S Twin Motorized Elevation Column offers broadcast quality performance and height range at a competitive price.

Setting up in minutes, the Lifto 25/S Twin with an easy and reliable hardwire hand control unit allows for continuous movement throughout the range and 3 position pre-settings. The perfect solution for small studios, educational, live events and House Of Worship.

The easy and reliable control unit is connected via wire or optional Bluetooth. The manual control has 3 position pre-settings for fast routine repositioning.

Lifto 25/S Twin Motorized Elevation Column performs great versatility in height range, from 118 cm (46.8") minimum to 380 cm (150") maximum. The patented Smart Deployment Series (SDS) two stage tripod with Smart-Stop Mid-Level spreader are engineered for great stability and rigidity . The extremely smooth and silent motorized column offers a four stage, 132 cm (52") stroke at 20 kg/44 lbs capacity.

The Lifto 25/S Twin can be converted to a Lifto 25/S removing the APTZ008 column.

The Lifto 25/S Twin unit can be packed in a compact high quality wheeled case for easy transportation, available to order as an accessory.

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.