

Datavideo PTC-305G

ProdCode: DATAPTC305G

4K 20x 12G NDI Tracking PTZ Camera - Dark Grey



[\[Download Images\]](#) (.zip file)

Features

- 4K 20x 12G NDI Tracking PTZ Camera
- 4K PTZ Camera with 20X Optical Zoom Auto Tracking and 12G-SDI
- Simultaneous Outputs
- Custom Auto Object Tracking
- Smart PTZ Speed Adaptation
- Talent Position: Center / Left Side / Right Side
- 20x Optical Zoom
- Multiple Network Protocol with Dual Stream Function
- Supports H.264/H.265 Video Compression
- Power over Ethernet
- Tally Light

4K PTZ Camera with 20X Optical Zoom Auto Tracking and 12G-SDI

The PTC-305G is a professional-grade PTZ camera designed for broadcast applications, featuring 12G-SDI output. This allows it to deliver high-quality 4K 60p video over a SDI cable, making it ideal for professional broadcasting environments

where top-tier video quality and seamless integration are paramount. Additionally, the PTC-305G is equipped with a 20X optical zoom, allowing for detailed close-ups and precise framing even from a distance.

The PTC-305 series supports dual streaming output, making it ideal for professional broadcast and A/V market applications, and facilitates easy streaming to platforms like Facebook (RTMPS), YouTube, and dvCloud. Moreover, the PTC-305G includes integrated NDI control functionality, providing enhanced flexibility and efficiency for modern live production environments.

Compliant with the ONVIF Profile S standard, the PTC-305G ensures compatibility and interoperability in various network video environments. For diverse workflow needs, Datavideo offers extended models like the PTC-305T 4K HDBaseT.

Simultaneous Outputs

Connect your PTC-305G to multiple devices in your workflow for flexibility. All the outputs are active at the same time.

Quick Access to Camera's Auto Tracking

You will be allowed direct access to auto tracking via various external controllers such as the supplied RMC-1AT remote control and DVIP controllers (RMC-300A, PTC View Assist, etc.)

In addition to camera controllers, you can also easily enable auto tracking on smart switchers which include iCAST mini, SHOWCAST 100, etc as well as complete solution systems like ZR-1 Hybrid Video Production Solution.

Custom Auto Object Tracking

If you are filming multiple people, you can designate a person for auto tracking. Once linked to the camera, only the designated person will be tracked, avoiding interferences such as the desks, people coming back and forth, large objects, etc.

Smart PTZ Speed Adaptation

The integrated PID algorithm is able to detect the movement speed of the identified object and automatically adjust the camera's corresponding pan, tilt and zoom speeds in such a way that the lens movement will be smooth, avoiding common camera lens movement problems like jerky movements or unpredicted halts.

Talent Position: Center / Left Side / Right Side

The positioning of talent depends on the videographer's creativity and intent rather than strict rules. Different positions can convey various emotions, messages, or visual effects. A centered composition provides a sense of stability and balance, suitable for scenes that require highlighting the main subject. Videographers may also place the talent on the left third or right third of the frame, leaving adequate space in the foreground to showcase the talent's sight direction or potential future possibilities.

Quick Selection of Full Body / Half Body / Close-up

All of the PTC-305 camera series include RMC-1AT controller. User can quickly select full-body, half-body and close up framing, making it easy to change the shooting scene and framing requirements.

Broadcast Quality 4K Resolution

With built-in 1/1.8" CMOS sensor, supports resolution up to 2160p 50/60.

Superior Optical Performance

The PTC-305 series camera has 20x Optical Zoom and 16x Digital Zoom with the f1.58 wide open aperture.

Low Noise in Low Light

Advanced 3D noise reduction technology is also used to further reduce the noise while ensuring image sharpness.

Multiple Simultaneous Video Outputs

Supports simultaneous HDMI 2.0 and IP output up to 2160p 50/60 and also 12G-SDI output up to 2160p 60/50.

Multiple Network Protocol with Dual Stream Function

Support RTSP and RTMPS protocols, easy to stream directly to two different CDN platforms and Datavideo dvCloud as well.

Supports H.264/H.265 Video Compression

Support compression of resolution up to 3840x2160 with frame up to 59.94, 60fps and the second channel 720x480p compression. AAC, MP3 and PCM audio compression also supported.

Power over Ethernet

The PTC-305 series supports PoE for easy installation. No need to find local power outlets or hire an electrician to install outlets wherever you want to mount your camera. Simply run a single CAT-6 cable to power your PTC-305 series camera.

Tally Light

Green and red lights tally to show the preview and program status for broadcast applications.

Simply Enable Auto Tracking with Your IR Remote Control

RMC-1AT PTZ Controller. All you need is a remote control to set and control all four cameras and save the four presets.

In the box:

- 1x PTC-305G product
 - 1x IR remote controller
 - 1x Ceiling mount bracket-A
 - 1x Ceiling mount bracket -B
 - 6x Ceiling mount bracket screw M3*4mm
 - 1x DC 12V Power Adaptor
 - 1x Safety cable
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.