

Datavideo TLM-102

ProdCode: DATATLM102

Dual 10" Monitor



[\[Download Images\]](#) (.zip file)

Features

- Dual 10" Monitor with 1280*800 IPS Panel Resolution.
- Dual Monitor with 4RU Rack Mount.
- Support 3G-SDI video input with loop-through output.
- Support HDMI video input with loop-through output.
- Support OSD menu for various functions including Column (YRGB peak), time code, waveform, vector scope, audio level meter, peaking, zoom, pix to pix, underscan, check field, etc.
- Support SDI & HDMI Cross Conversion.
- Individual adjustment of Brightness, Contrast, Color Saturation and LED Backlight Level for each monitor.
- Colour temperature menu option has 4 modes (6500K, 7500K, 9300K and user defined)
- Support front panel headphone jack.
- Support 15 pin Tally input interface.
- Support User-definable function buttons F1 and F2

Specifications

- **Screen:** 10.1" LCD
- **Chassis:** 4RU Rack Mount
- **Resolution:** 1280 x 800
- **Viewing Angle:** (H) 170° | (V) 170°
- **Luminance/Contrast:** 300 cd/m² | 800:1
- **Video Inputs:** 1x 3G/HD/SD-SDI | 1x HDMI
- **Loop Through:** 1x 3G/HD/SD-SDI | 1x HDMI
- **Supported Input Resolutions:** 1080p (23.98/24/25/29.97/30/50/59.94/60Hz), 1080i (50/59.94/60Hz), 720p (23.98/24/25/29.97/30/50/59.94/60Hz), 480i (NTSC), 576i (PAL)
- **Aspect Ratio:** 16:9, 4:3
- **Tally LED:** Live (Red) | Cued (Green)
- **Audio In/Out:** Embedded Audio on SDI and HDMI | Headphone Jack
- **Special Features:** Time Code, Waveform, Vector Scope & Audio Level Meter, Peaking, Zoom, Pix to Pix, Underscan, SDI, HDMI Cross Conversion
- **Power:** DC 12V, 26 watts

The Datavideo TLM-102 Dual 10" monitor is a 4RU Rack mount dual monitor which is designed for the broadcast quality monitoring application. Datavideo TLM-102's 4RU rack design, SDI and HDMI inputs and outputs and different mounting methods make it the best solution for various applications such as live vans, on-site monitoring and video wall. The TLM-102 brings high quality and user friendly viewing experience for users via its excellent display quality and advanced auxiliary functions.

In the box:

- 1 x TLM-102
- 1 x DC 12V Power adapter
- 1 x Tally Connector
- 1 x Manual

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk

- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch.
Thank you for your continued support.