

Densitron UReady 2U Monitor

ProdCode: DENDM163BD

2U 19inch Rack mount ready TFT display with capacitive touch for Broadcast applications



[\[Download Images\] \(.zip file\)](#)

Features

2U 19" Rack mount ready TFT display with capacitive touch for Broadcast applications. It can be used for signal and picture monitoring, or a control system with the help of multi-touch PCT, or a combination of both. Densitron provides a 16.3" high resolution (1920 x 285) display, which allows multiple video picture monitor and audio level displays – side-by-side. Projected Capacitive Touch functionality allows the device to be interactive with Common signal interfaces, such as: Display port, DVI and VGA are used for video signals; and USB for touch screen.

- 2U 19" Rack mount ready TFT display with capacitive touch for Broadcast applications
- Packaged into a single 2RU 19" rack metal chassis
- Single 12V power supply
- Resolution: 1920 x 285 px
- 24-bit colour depth of 16.4M colours
- 700cd/m² peak luminance and adjustable backlight
- Utilising MVA technology which offers 89/89/89/89 symmetric viewing

- Continuous operation
 - Designed to operate continuously with backlight half-life of 50k hours and a temperature range of 0°C to +50°C
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.