

# **Lumens VC-B11U**

ProdCode: LUMVCB11U

Zoom Certified Video Conference Webcam



[Download Images] (.zip file)

#### **Features**

- Zoom Certified Video Conference Webcam
- Clear images with 4K sensor, fixed-lens, and WDR
- Effectively capture human voice up to 5 meters
- Hands-free auto framing to include all participants in a perfect view
- Easily control the camera by a mini remote controller or software
- Compatible with leading UC platforms and wireless presentation tools

# **UC and VC Integration**

Certified by **Zoom** and compliant with **Barco ClickShare Conference**, the VC-B11U is compliant with all major video conferencing applications and unified collaboration platforms. It can even be used as a live video source within live production and streaming tools such as **YouTube Live**, **vMix**, and **OBS Broadcast**.

# **Pro Quality**

The Lumens VC-B11U is a professional grade USB camera designed for small to

medium sized meeting rooms. Equipped with a 4K sensor, advanced image processing and reliable auto-focus, the camera outputs perfectly exposed video images enabling small groups to communicate effectively with remote teams. Featuring WDR (wide dynamic range) technology, the unit ensures that each participant is clearly visible on screen, even in difficult lighting conditions.

## **Auto-Configuration**

The VC-B11U's auto-framing function immediately detects participants in a meeting. It dynamically adjusts its frame of angle to include all delegates, re-framing the view if participants join or leave during the meeting. There's no need for a remote controller to set the field of view – it's all automatically taken care of by the camera.

### Sound

The camera's dual microphones are designed to pick up voices from up to 5 meters distance. This makes the VC-B11U suitable for sharing round table meetings or discussions in conference breakout rooms.

## **Specifications**

• Camera Type: ePTZ

Dimensions: Without Clip: 1.2" x 8.3" x 1.4"(30 x 210 x 35 mm) With Clip: 1.9" x 8.3" x 2.9" (47.4 x 210 x 73.6 mm)

• Image Sensor: 1/2.8" 8.57MP CMOS

• **NDI**: No

• Output: USB 3.0 Type C (USB 2.0 Compatible)

• **Preset**: 64

Video Format: 3840x2160 30/25 fps, 1920x1080 30/25 fps, 1280x720 30/25 fps, 640x360 30/25 fps, 320x240 30/25 fps

• Weight: 0.5kg

# **Need Further Support?**

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

#### **Contact Us:**

- Marketing marketing@holdan.co.uk
- Sales sales@holdan.co.uk

<ul> <li>Technical Enquiries - <u>techsales@holdan.co.uk</u></li> <li>Request Demo product loans - <u>demo@holdan.co.uk</u></li> </ul>
We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.