

Lumens VC-BC301P

ProdCode: LUMVCBC301PB

Lumens ePTZ block camera: 4K/60, HDMI, USB 3.0, IP control, tally



[\[Download Images\] \(.zip file\)](#)

Features

- 4K IP POV Camera
- High Quality 4K 60fps Images
- Compact Design with Tally Light
- Supports ePTZ Function
- HDMI, Ethernet, and USB3.0 Video Outputs
- 5 Year Warranty

4K 60fps Image Quality

The VC-BC301P IP POV Camera is built with a 1/1.8" high sensitive SONY sensor which delivers 4K 60fps ultra-clear image quality.

Supports ePTZ Function

With VC-IR01 remote control, you can easily control the VC-BC301P camera with features including pan, tilt, zoom, and preset function.

IP (PoE), USB, HDMI Video Outputs

The VC-BC301P camera supports IP (PoE), HDMI and USB video outputs. The PoE allows flexible and simple installation.

Tally Light & Compact Design

The VC-BC301P built-in tally light turns on when it is in operation to provide visual confirmation to the presenter or director. It can be easily integrated into any environment with a compact design.

In the box:

- Camera
- Instruction for installation
- Power Adapter
- AC Power Cord Bracket accessory kit
- Bracket accessory kit

Specifications

- **Camera Type:** ePTZ
 - **Dimensions:** 113 x 70 x 51 mm
 - **Image Sensor:** 1/1.8inch 9.17 MP CMOS
 - **NDI:** No
 - **Output:** HDMI 2.0, Ethernet, USB 3.0 (USB 2.0 compatible)
 - **Video Format:** Resolution : 4K / 1080p / 720p
Frame Rate : 59.94 / 50 / 29.97 / 25
 - **Weight:** 350g
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch.
Thank you for your continued support.