

Slidekamera AION 2D

ProdCode: MRMCHGNST2

2-axis Controller (PAN, TILT)



[\[Download Images\]](#) (.zip file)

Features

- 2-axis Controller (PAN, TILT)
- Ideal for cranes/jibs remote heads (X-HEAD, BULL HEAD)
- 3 memory banks to store and playback motion trajectory

Basic features

- Intuitive control of the two axes X and Y with joystick
- Speed of rotation proportional to joystick swing
- Two methods of joystick work - LINEAR and LOGARITHMIC
- INVERT - change the direction of rotation for each axis separately
- Knobs SPEED and DAMPING
- Calibration of each axis
- 3 memory banks to store and playback motion trajectory
- Playback the saved trajectory in LOOP
- Playback the recorded motion from the saved starting point

The connection of the AION 2D Controller with a steering and powered cable: 5

meters. Electric connectors sockets and the power switch are located on the top wall of the controller housing. The 1/4" socket in the base of the controller enables it to be mounted to the cart with a 8" or 11" VARIO ARM Classic.

TECHNICAL SPECIFICATION

- Weight: 400g
 - Dimensions: Width: 110mm
 - Length: 185mm
 - Height (with a joystick): 80mm
 - Compatible devices: X-HEAD, BULL HEAD
 - Three memory banks: M1: 200sec, M2: 100sec, M3: 100sec
 - Supply voltage: 10..17V DC min 12W
 - Operating temperature range: 0°-40°C
 - Recommended relative humidity: <90%
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.