

Panasonic AW-HR140

ProdCode: PANAWHR140EJ

Full HD Rugged Outdoor PTZ Camera



[\[Download Images\]](#) (.zip file)

Features

- Full HD Rugged Outdoor PTZ Camera
- Enclosed in an IP65 protected case that eliminates the need for a separate housing
- Full-HD 3 MOS Sensor
- Optical 20x + Digital 10x Zoom
- Water & Dust Resistant (IP65) Case
- Built-In Lens Wiper

The camera features 1/2.86-type full HD 3MOS sensors and a motorized 20x zoom lens. Sophisticated image processing affords high sensitivity with low noise and horizontal resolution of 1000 TV lines. The water and dust-resistant case likewise resists salt damage and features a wiper. Stable images are captured with vibration compensation provided by the newly-developed Dynamic Image Stabilizing System (D.I.S.S.), a valuable asset in the event of high winds or related unstable weather conditions.

The HR140 boasts haze-reduction technology--valuable for outdoor environments

such as weather reporting--for ensuring optimal image reproduction. In certain situations, picture contrast may be low as result of environmental fog or haze conditions, and the Haze Reduction function will optimize camera image settings appropriately to assure that the subject of shooting is as clear as possible.

Output formats include 1080/59.94p, 1080/50p, 1080/59.94i, 1080/50i, 1080/29.97p, 1080/25p, 1080/23.98p, 1080/29.97PsF, 1080/25PsF, 1080/23.98PsF, 720/59.94p and 720/50p.

Using an IP connection, up to 100 HR140 cameras can be controlled by the AW-RP120G/RP50 remote camera controller via a switching hub. One camera can also be operated by up to five remote camera controllers via IP connection.

In the box:

- 1 x AW-HR140
- 4 x Hexagonal Bolts M8 x 30mm (Includes 4 x M8 Washers, 4 x M8 Spring Washers)
- 1 x Cable Cover
- 1 x Washer Nozzle Mount Bracket
- 1 x Drop Prevention Wire (Includes 1 x M4 x 10mm Mounting Screw)

Specifications

- **Camera Control Unit:** AW-RP120, AW-RP50, AV-HLC100, AK-HRP200G, AK-HRP1000
- **Dimensions:** (W x H x D) 258 x 357 x 397mm / 10-5/32 x 14-1/16 x 15-5/8"
- **Image Sensor:** 1/2.86 type Full-HD 3MOS
- **NDI:** No
- **Output:** 3G-SDI & HD-SDI
- **Preset:** Up to 100
- **Remote Control Interface:** RS-422
- **Video Format:** 1080/59.94p | 1080/29.97p | 1080/23.98p | 1080/50p | 1080/25p | 1080/59.94i | 1080/50i | 1080/29.97PsF | 1080/25PsF | 1080/23.98PsF | 720/59.94p | 720/50p
- **Weight:** Approx. 9.0kg / 19.8lbs
- **Zoom:** Optical zoom: 20x | Digital zoom: 10x

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries

or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch.
Thank you for your continued support.