

SRP: £1799.00 | List: £1499.00 | EAN: 5025232982523

Panasonic LUMIX S-R100500E

ProdCode: PANSR100500E

Lumix S Super-Telephoto Zoom Lens 100-500mm/ F5-7.1 OIS - L-Mount

[\[Download Images\]](#) (.zip file)

Features

- Lumix S Super-Telephoto Zoom Lens 100-500mm/ F5-7.1 OIS - L-Mount
- **Super telephoto zoom**
100-500mm, F5-7.1; supports teleconverter, enabling up to 1000mm focal length
- **Image stabilization**
Achieves highly effective image stabilization with 7.0-stop Dual I.S. 2
- **Compact design**
Ultra-telephoto zoom reaches in a remarkably compact 196.1mm design
- **High-speed AF**
high-precision AF powered by a Dual Phase Linear Motor
- **Ideal for video**
Suppression of focus breathing silent focusing
- **Toughness**
Dust-, splash and freeze resistant

The LUMIX S-R100500 covers a focal length from 100 to 500mm and supports teleconverters, enabling telephoto shooting of up to 1000mm. It delivers high resolution

and beautiful bokeh across the entire zoom range, to capture stunning images and footage in a wide variety of shooting scenarios including wildlife, motorsports, and landscapes.

With an optimized lens element arrangement and Dual Phase Linear Motor, the lens achieves a remarkably compact design, while delivering impressive ultra-telephoto performance. Highspeed, high-precision, and silent autofocus, combined with Dual I.S. 2 image stabilization supporting up to 7.0 stops, ensures exceptional portability and handheld shooting support.

The lens is also designed for intuitive operation, featuring a customizable focus ring and a focus button. To meet the growing demand for video production, the lens incorporates features such as focus breathing suppression and micro-step aperture control for smooth exposure transitions, supporting high-quality video performance.

In the box:

- S-R100500E
- Lens cap
- Lens rear cap
- Lens hood
- Tripod mount

Specifications

- **Closest Focusing Distance:** W: 0,8m / T: 1,5m
 - **Diagonal Angle of View:** 24°(Wide) - 5.0°(Tele)
 - **Dimensions:** 92,0 x 196,1 mm
 - **Filter Size:** 82 mm
 - **Focal Length:** 100-500mm (up to 1000mm with teleconverter (sold separately))
 - **Lens Construction:** 19 elements in 12 groups (2 UED lens, 2 ED lenses, 2 UHR lenses)
 - **Maximum Aperture:** F5 (Wide) - F7.1 (Tele)
 - **Maximum Magnification:** W: 0,16x / T: 0.36x
 - **Minimum Aperture:** F29 (Wide) - F40 (Tele)
 - **Mount Type:** L-Mount
 - **No. Diaphragm Blades:** 11 diaphragm blades / Circular aperture diaphragm
 - **Optical Image Stabilizer:** O.I.S / DUAL IS compatible (up to 7 stops* at tele*)
 - **Weather Proof:** Yes
 - **Weight:** 1.285 g
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.