

Panasonic LUMIX S-R1635

ProdCode: PANSR1635E

LUMIX S PRO 16-35mm F4 Wide Zoom Full-Frame L Mount Lens

[\[Download Images\]](#) (.zip file)

Features

- **LUMIX S PRO CAMERA LENS**
16-35mm wide angle zoom L-mount lens for LUMIX S Series Full-Frame digital mirrorless cameras
- **VIDEO SUPPORT**
Excels in video recording performance with a mechanism to suppress focus breathing and micro-step aperture control for smooth exposure change
- **LENS ELEMENTS**
12 elements in 9 groups, the use of 3 aspherical lenses, an ED (Extra-low Dispersion) lens and a UHR (Ultra-High Refractive Index) lens with optimum alignment to achieve high MTF performance
- **RUGGED LENS DESIGN**
Dust/splash*/freeze-resistant design withstands heavy field use under harsh conditions for high mobility (*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.)
- **FOCUS CLUTCH MECHANISM**
Enables instant AF/MF switching, accurate manual focusing and suppressed

focus breathing

The LUMIX S PRO 16-35mm F4 (S-R1635) is a versatile wide zoom lens that provides high resolution images despite its compact, lightweight profile. It boasts high descriptive performance in both photo shooting and video recording.

For the AF actuator, a double-magnet linear motor is integrated. It features high power despite its small size, achieving a maximum 480 fps high-speed sensor drive. This realizes fast, high-precision AF to ensure that photo opportunities are never missed. Adoption of a focus clutch mechanism enables instant AF/MF switching and accurate manual focusing.

The LUMIX S PRO 16-35mm F4 also excels in video recording performance with a mechanism that suppresses focus breathing, which was a fatal problem in all interchangeable lenses designed for still image photography.

(*Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.)

Specifications

- **Closest Focusing Distance:** 0.25m / 0.82ft
- **Diagonal Angle of View:** 107°(Wide) - 63°(Tele)
- **Filter Size:** ∅77mm
- **Focal Length:** f=16-35mm
- **Maximum Aperture:** F4
- **Maximum Diameter:** ∅85mm / 3.34inch
- **Maximum Magnification:** Approx.0.23x
- **Minimum Aperture:** F22
- **Mount Type:** L
- **Optical Image Stabilizer:** No
- **Weight:** approx.500g /17.63 oz (excluding lens cap, lens rear cap and lens hood)

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch.
Thank you for your continued support.