

Panasonic LUMIX S-R2060E

ProdCode: PANSR2060E

LUMIX S 20-60mm F3.5-5.6 L-Mount Lens

[\[Download Images\]](#) (.zip file)

Features

- LUMIX S 20-60mm F3.5-5.6 L-Mount Lens
- Compact, lightweight standard zoom lens that covers ultra-wide 20mm to standard 60mm focal length
- Ensures smooth, high-quality video recording due to a mechanism that suppresses focus breathing

Convenience and Versatility Condensed Into One

This compact, lightweight standard zoom lens features an ultra-wide 20mm to 60mm zoom range, offering outstanding flexibility for shooting stills and videos. Whether shooting Landscapes, still-life or your family this lens can adapt to your requirements.

Excellent Close-up Performance

Shooting indoors can often mean restricted space in which to work, with a closest focusing distance of just 0.15m** and a maximum magnification of 0.43x* means that if your space is limited your creativity does not need to be.

* At 0.15m with focal length 26mm.

** Closest focusing distance 0.15m (at 20-26mm) / 0.4m (at 60mm).

Rugged Design for Bad Weather Conditions

From the flourine coating helping preventing water and oil from sticking to the front element, through to the dust- and splash-resistant design to withstand use in harsh conditions, down to -10 degrees Celsius, this lens has been designed to keep you shooting.

* Dust and Splash Resistant does not guarantee that damage will not occur if this lens is subjected to direct contact with dust and water.

Built with Video in mind

This lens has been designed for the video user, the fast and silent focusing motor allows you to shoot without disturbing your subject. While smooth aperture changes and minimised Focus breathing ensure that transitions while shooting are not disruptive.

Lens Construction

The optical design of this lens consists of 11 elements in 9 groups, including 2 ASPH, 3 ED, and 1 UHR lenses to minimize aberrations and ensure superb resolution and image quality.

MTF Chart

Offering outstanding image quality throughout the entire zoom range this lens offers creative flexibility in a wide variety of shooting conditions, making it an ideal lightweight everyday lens for the LUMIX full-frame system.

* For lenses that are capable of compensating distortion, the horizontal axis shows the distance from the center of the corrected image.

In the box:

- 1x S-R2060E Lens
- 1x Lens cap
- 1x Lens rear cap
- 1x Lens hood

Specifications

- **Closest Focusing Distance:** 0.15m/0.49ft (at focal length 20-26mm) / 0.4m/1.31ft (at focal length 60mm)
 - **Diagonal Angle of View:** 94°(Wide) - 40°(Tele)
 - **Filter Size:** \varnothing 67mm
 - **Focal Length:** f=20-60mm
 - **Lens Construction:** 11 elements in 9 groups (2 aspherical lenses, 3 ED lenses, 1 UHR lens)
 - **Lens Type:** Zoom
 - **Maximum Aperture:** F3.5 (Wide) - F5.6 (Tele)
 - **Maximum Diameter:** \varnothing 77.4mm / 3.05inch
 - **Maximum Magnification:** 0.43x
 - **Minimum Aperture:** F22
 - **Mount Type:** L
 - **No. Diaphragm Blades:** 9 diaphragm blades
 - **Optical Image Stabilizer:** N
 - **Weather Proof:** Dust and Splash Resistant
 - **Weight:** Approx. 350g / 12.35oz (excluding lens cap, lens rear cap and lens hood)
-

Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

Contact Us:

- Marketing - marketing@holdan.co.uk
- Sales - sales@holdan.co.uk
- Technical Enquiries - techsales@holdan.co.uk
- Request Demo product loans - demo@holdan.co.uk

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.