

# Panasonic LUMIX S-R24105

**ProdCode: PANSR24105E**

L-Mount 24-105mm Standard Zoom Lens

[\[Download Images\]](#) (.zip file)

## Features

- L-Mount 24-105mm Standard Zoom Lens
- **Lumix S Camera Lens**  
24-105mm standard focal macro zoom F4 L-Mount for LUMIX S Series Full-Frame L-Mount digital mirrorless cameras.
- **O.I.S. Stabilization**  
Complies with LUMIX camera body I.S.; 5-Axis Dual I.S. 2 [1] makes it possible to use 6-stop slower shutter speed [2]
- **Lens Elements**  
16 lenses in 13 groups; 2 aspherical lenses and 2 ED (Extra-low Dispersion) lenses effectively suppress chromatic aberration and achieve high resolution.
- **Macro Lens**  
0.5x macro shooting with a minimum focusing distance of 0.3m so you can photograph small subjects at very close distances.
- **Rugged Lens Design**  
Dust/splash\*/freeze-resistant design withstands use under harsh conditions for high mobility.

The Panasonic LUMIX S-R24105 24-105mm F4 Macro Lens with O.I.S. is a versatile standard zoom lens covering wide-angle to medium-telephoto with high-descriptive performance across the entire zoom range. The LUMIX S Macro Lens enables 0.5x macro shooting with a minimum focus distance of 0.3m so you can photograph small subjects at very close distances. This Macro lens is compatible with the interchangeable Full Frame L-Mount.

The O.I.S. (Optical Image Stabilizer) in the lens effectively compensates for hand-shake movement, making it easy to shoot without a tripod. This Panasonic LUMIX lens offers high-precision Auto Focus to capture every photo opportunity. The focus clutch mechanism enables both instant AF/MF switching and accurate manual focusing. Focus breathing is suppressed making it an excellent choice for video recording.

Camera performance, lightweight construction, and Dust/Splash\*/Freeze-Resistant Design are some of the features you'll enjoy while shooting with the Panasonic LUMIX S Series lens.

DISCLAIMERS: [1] 5-Axis Dual I.S. 2 can be used with the camera LUMIX S1R and S1, as of February 1, 2019. [2] Based on the CIPA standard [Yaw/Pitch direction: focusing distance f=105mm, when LUMIX S1R is used.

## Specifications

- **Closest Focusing Distance:** 0.30m / 0.98ft
  - **Diagonal Angle of View:** 84°(Wide) - 23°(Tele)
  - **Dimensions:** Length: Approx. 118mm / 4.65" (from the tip of the lens to the base side of the lens mount)
  - **Filter Size:**  $\varnothing$ 77mm
  - **Focal Length:** 24-105mm
  - **Geared Focus / Iris:** No
  - **Lens Construction:** 16 elements in 13 groups
  - **Lens Type:** Zoom
  - **Maximum Aperture:** F4.0
  - **Maximum Diameter:**  $\varnothing$ 84mm / 3.31"
  - **Maximum Magnification:** Approx. 0.5x
  - **Minimum Aperture:** F22
  - **Mount Type:** L
  - **No. Diaphragm Blades:** 9 diaphragm blades
  - **Optical Image Stabilizer:** Yes
  - **Weather Proof:** Dust and Splash Resistant
  - **Weight:** Approx. 680g / 23.99oz (excluding lens cap, lens rear cap and lens hood)
-

## Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

### Contact Us:

- Marketing - [marketing@holdan.co.uk](mailto:marketing@holdan.co.uk)
- Sales - [sales@holdan.co.uk](mailto:sales@holdan.co.uk)
- Technical Enquiries - [techsales@holdan.co.uk](mailto:techsales@holdan.co.uk)
- Request Demo product loans - [demo@holdan.co.uk](mailto:demo@holdan.co.uk)

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.