

## Panasonic LUMIX S-S24

**ProdCode: PANSS24E**

LUMIX S 24mm F1.8 L-Mount Lens

[\[Download Images\]](#) (.zip file)

### Features

- LUMIX S 24mm F1.8 L-Mount Lens
- Superior optical performance and advanced functionality in a wide-angle fixed focal length lens
- F1.8 large-aperture wide-angle fixed focal length lens with a compact, lightweight design
- Dust, splash and freeze-resistant design
- Excellent focusing performance for both photos and videos

**Richer, more detailed stills. Smoother, more compelling video.**

Introducing the LUMIX S F1.8 Series 24mm lens. In a compact and lightweight form, it features an uncompromising optical design with the power to capture broad landscapes with corner-to-corner sharpness. Focus breathing inhibition and seamless exposure control contribute to the beautifully smooth video capture. Expressive power is perfectly aligned with the rest of the F1.8 Series, so even as you change lenses, your sequence of images will boast high quality continuity.

## Dust, splash and freeze-resistant design

The LUMIX S 24mm F1.8 is designed to keep shooting in the toughest conditions thanks to its dust- and splash-resistant construction and allowing you to shoot in temperatures as low as -10 °C.

## Ideal for video recording

The lens offers fast, accurate autofocus and smooth aperture changes, critical for the modern content creator, allowing you to record beautiful 4K video and stills without disturbing your subject.

## S-S24 lens construction

The optimized configuration has 12 elements in 11 groups, including 3 ASPH, 1 UED and 3 ED lenses to minimize aberrations and ensure superb resolution.

## In the box:

- Lens cap
- Lens rear cap
- Lens hood

## Specifications

- **Closest Focusing Distance:** 0.24m / 0.79ft
- **Diagonal Angle of View:** 84°
- **Dimensions:** Approx. 82.0mm / 3.23inch
- **Filter Size:**  $\varnothing$ 67mm
- **Focal Length:** f=24mm
- **Lens Construction:** 12 elements in 11 groups (3 aspherical lenses, 1 UED lens, 3 ED lens)
- **Maximum Aperture:** F1.8
- **Minimum Aperture:** F16
- **Mount Type:** L-Mount
- **No. Diaphragm Blades:** 9 diaphragm blades / Circular aperture diaphragm
- **Weight:** Approx. 310g / 0.68lb

---

## Need Further Support?

If you have any questions or require additional support regarding this product release, please do not hesitate to contact us. Our team is here to assist you with any inquiries

or provide further information or marketing collateral as needed.

**Contact Us:**

- Marketing - [marketing@holdan.co.uk](mailto:marketing@holdan.co.uk)
- Sales - [sales@holdan.co.uk](mailto:sales@holdan.co.uk)
- Technical Enquiries - [techsales@holdan.co.uk](mailto:techsales@holdan.co.uk)
- Request Demo product loans - [demo@holdan.co.uk](mailto:demo@holdan.co.uk)

We value your partnership and are committed to ensuring a successful product launch.  
Thank you for your continued support.