

## Wise Advanced PTS-1024

**ProdCode: WISEPTS1024**

Portable SSD - 1TB with USB 3.1 Type-C

[\[Download Images\]](#) (.zip file)

### Features

- Portable SSD - GB
- USB 3.1 Gen2, Type-C port
- Speeds of up to 550 MB/s read and 520 MB/s write
- Optimizing for 4K RAW recording up to 60 frame per second
- Certified by Blackmagic Design (256GB and 512GB)
- Hot shoe mount, Velcro strap and USB 3.1 type C to C cable included

### THE solid state drive for 4K video production

Unlike general solid state drives for personal computers (PC), Wise Portable & CINEMA SSDs are especially designed for the challenging demands of the video industry. It is developed to be not only fast, but also steady and compatible with a wide range of 4K professional cameras and external monitors.

- **Especially For Video Production**

Wise Portable & CINEMA SSDs are built for video shooting with both extremely smooth data streaming and fast recording speed for 4K RAW.

- **Speeds Of Up To 550 Mb/s Read And 520 Mb/s Write**

The high-speed performance of the SSD pushes the SATA interface to the limit. The sustained write speed of up to 520 GB/s optimizes your 4K video productions. With an industry-leading read speed of up to 550 MB/s, you are able to transfer large RAW files in a flash.

- **Ultimate Durability**

Wise Advanced Portable & CINEMA SSDs are water-proof, dust-proof, shock-proof, X-ray proof and can be operated in temperatures ranging from 32°F to 158°F (0°C to 70°C).

Model	<a href="#">PTS-512</a>	<a href="#">PTS-1024</a>	<a href="#">PTS-2048</a>
Capacity	512GB	1TB	2TB
Read Speed	550 MB/s	550 MB/s	550 MB/s
Write Speed	520 MB/s	520 MB/s	520 MB/s
Interface	SATA Revision 3.0 (6 Gb/s)		
Dimensions	102 x 32 x 9 mm		
Weight	29g / 0.06 lbs		
Operating temperature	32°F to 158°F (0°C to 70°C)		
Storage temperature	-13°F to 185°F (-25°C to 85°C)		

#### In the box:

- 1x 1TB Portable SSD
- 1x USB 3.1 Type C to C Cable
- 1x Hot Shoe Mount
- 1x Velcro Strap
- Quick Start Guide

#### Specifications

- **Capacity:** 1TB
- **Dimensions:** 102 x 32 x 9mm
- **Operating Temperature:** 32°F to 158°F (0°C to 70°C)
- **Read Speed:** 550 MB/s
- **Storage Temperature:** -13°F to 185°F (-25°C to 85°C)
- **Weight:** 29g / 0.06 lbs
- **Write Speed:** 520 MB/s

---

#### Need Further Support?

If you have any questions or require additional support regarding this product release,

please do not hesitate to contact us. Our team is here to assist you with any inquiries or provide further information or marketing collateral as needed.

**Contact Us:**

- Marketing - [marketing@holdan.co.uk](mailto:marketing@holdan.co.uk)
- Sales - [sales@holdan.co.uk](mailto:sales@holdan.co.uk)
- Technical Enquiries - [techsales@holdan.co.uk](mailto:techsales@holdan.co.uk)
- Request Demo product loans - [demo@holdan.co.uk](mailto:demo@holdan.co.uk)

We value your partnership and are committed to ensuring a successful product launch. Thank you for your continued support.